



**Digital Signage** indoor freestanding display screen with concise design and reliable performance is a perfect solution for advertising and public services.



**Slim Design**

### Non-Touch Digital Signage Standee

Standee Size	TTPL55NT
Operating System	Android 9.0/10.0/11.0
Maximum resolution	2/3/4GB RAM, 16/32 GB Storage
Aspect Ratio	3840*2160 (4K UHD)
Brightness (nits)	16:9
Native Contrast Ratio	500cd/m2
View angle	4000 : 1
Surface Haze	178°/178°(H/V)
Hard Coating	28%
Duty Cycle	3H
Screen Protection	24*7
CPU	Toughened Glass (optional)
GPU	Quad Core ARM Cortex- A35
Life Time(hrs.)	ARM Mali-G31 MP2, Concurrent Multi-Core Processing
USB	≥ 50,000
HDMI Port	USB 2.0 x 2
Line Out	HDMI 2.0 x3
RJ45	1 (3.5mm jack)
RS232	1 x RJ45 (100/10Mbps)
Antenna	Yes
Speaker	Built-in WiFi / Bluetooth
Power supply	10*2
Rated Power	100-240VAC, 50/60HZ
Working temperature	140W
Humidity	0°C~50°C
Cabinet color/appearance	20%~80%
CMS (Optional)	Powder Coated Metal Sheet /Black
Content Sharing through Pen- Drive	Yes
Mounting arrangement	Yes
	Floor Mount

\*Product weight and dimension are approximately and features & technical specifications mentioned may change without any prior notice. All images are for representation only & may differ from actual product.